

**Natté 380P - white | linen (002008)**
**Technical info**
**FRONT**

**BACK**


<b>Widths</b>		250 cm   200 cm   320 cm
<b>Composition</b>		Polyester with PVC coating
<b>Openness factor</b>	NBN EN 410	5.00%
<b>Weight</b>	NF EN 12127	415.00 g/m <sup>2</sup>
<b>Thickness</b>	ISO 5084	0.42 mm
<b>Density</b>	ISO 7211/2	WARP 18.00 yarn/cm      WEFT 19.00 yarn/cm
<b>Color fastness to artificial light</b>	ISO 105 B02	>7
<b>Roll length</b>		30 m
<b>Cleaning</b>		With soapy water
<b>Confection</b>		By heat, high frequency or ultrasonic welding
<b>Fire classification</b>		
└ Europe	UNE-EN 13501-1:2007	B-s2,d0
└ France	NF P92-503	M2
└ Italy	UNI 9177	Class 1
└ Germany	DIN 4102	
└ Spain	UNE 13773	Clase 1

Natté 380P - white   linen (002008)		Technical info	
<b>Tear strength</b>	ISO 4674-1 methode 2		
↳ Original		WARP 4.10 daN	WEFT 3.65 daN
↳ After climatic chamber -30°C		WARP 3.95 daN	WEFT 3.80 daN
↳ After climatic chamber +70°C		WARP 4.25 daN	WEFT 3.65 daN
<b>Elongation up to break</b>	ISO 1421		
↳ Original		WARP 23.50 %	WEFT 20.50 %
↳ After color fastness to artificial light		WARP 23.00 %	WEFT 21.00 %
↳ After climatic chamber -30°C		WARP 23.00 %	WEFT 20.00 %
↳ After climatic chamber +70°C		WARP 24.00 %	WEFT 21.50 %
<b>Breaking strength</b>	ISO 1421		
↳ Original		WARP 165.00 daN/5cm	WEFT 155.00 daN/5cm
↳ After color fastness to artificial light		WARP 160.00 daN/5cm	WEFT 160.00 daN/5cm
↳ After climatic chamber -30°C		WARP 165.00 daN/5cm	WEFT 165.00 daN/5cm
↳ After climatic chamber +70°C		WARP 165.00 daN/5cm	WEFT 165.00 daN/5cm

**Front - Interior**

Natté 380P - white | linen (002008)

**Visual properties**

<b>Tv = Visual light transmittance</b>	19.90%
<b>Tuv = UV transmittance</b>	5.50%

**Solar energetic properties**

<b>As = Solar absorptance</b>	17.10%
<b>Rs = Solar reflectance</b>	58.50%
<b>Ts = Solar transmittance</b>	24.40%

**Fabric + glazing: G-factor**

	<b>G</b>	<b>Te</b>	<b>Qi</b>	<b>SC</b>
<b>Glazing A</b>	0.40	0.21	0.19	0.48
<b>Glazing B</b>	0.41	0.18	0.23	0.54
<b>Glazing C</b>	0.38	0.14	0.24	0.65
<b>Glazing D</b>	0.26	0.08	0.17	0.81

G = Total solar energy transmittance / Te = Direct solar transmittance / Qi = Secondary heat transfer factor / SC = Shading coefficient

**Visual comfort**

<b>Normal solar transmittance</b>	Class 3	Good effect
<b>Glare control</b>	Class 0	Very little effect
<b>Privacy night</b>	Class 1	Little effect
<b>Visual contact with the outside</b>	Class 3	Good effect
<b>Daylight utilisation</b>	Class 2	Moderate effect

**Thermal comfort G-factor = Total solar energy transmittance**

<b>Glazing A</b>	<b>Glazing B</b>	<b>Glazing C</b>	<b>Glazing D</b>
Class 1	Class 1	Class 1	Class 2

**Thermal comfort Qi-factor = Secondary heat transfer factor**

<b>Glazing A</b>	<b>Glazing B</b>	<b>Glazing C</b>	<b>Glazing D</b>
Class 2	Class 1	Class 1	Class 2

Class 0 = Very little effect / 1 = Little effect / 2 = Moderate effect / 3 = Good effect / 4 = Very good effect

**Back - Interior**

Natté 380P - white | linen (002008)

**Visual properties**

<b>Tv = Visual light transmittance</b>	19.90%
<b>Tuv = UV transmittance</b>	5.50%

**Solar energetic properties**

<b>As = Solar absorptance</b>	17.10%
<b>Rs = Solar reflectance</b>	58.50%
<b>Ts = Solar transmittance</b>	24.40%

**Fabric + glazing: G-factor**

	<b>G</b>	<b>Te</b>	<b>Qi</b>	<b>SC</b>
<b>Glazing A</b>	0.40	0.21	0.19	0.48
<b>Glazing B</b>	0.41	0.18	0.23	0.54
<b>Glazing C</b>	0.38	0.14	0.24	0.65
<b>Glazing D</b>	0.26	0.08	0.17	0.81

G = Total solar energy transmittance / Te = Direct solar transmittance / Qi = Secondary heat transfer factor / SC = Shading coefficient

**Visual comfort**

<b>Normal solar transmittance</b>	Class 3	Good effect
<b>Glare control</b>	Class 0	Very little effect
<b>Privacy night</b>	Class 1	Little effect
<b>Visual contact with the outside</b>	Class 3	Good effect
<b>Daylight utilisation</b>	Class 2	Moderate effect

**Thermal comfort G-factor = Total solar energy transmittance**

<b>Glazing A</b>	<b>Glazing B</b>	<b>Glazing C</b>	<b>Glazing D</b>
Class 1	Class 1	Class 1	Class 2

**Thermal comfort Qi-factor = Secondary heat transfer factor**

<b>Glazing A</b>	<b>Glazing B</b>	<b>Glazing C</b>	<b>Glazing D</b>
Class 2	Class 1	Class 1	Class 2

Class 0 = Very little effect / 1 = Little effect / 2 = Moderate effect / 3 = Good effect / 4 = Very good effect